

	<h1>ETRUSCA</h1>	<p style="text-align: center;"><b>SPECIFICATIONS</b></p> <hr/> <p style="text-align: center;">Rev. 0 – Ed. 1</p>
-----------------------------------------------------------------------------------	------------------	------------------------------------------------------------------------------------------------------------------

**SPECIFICATIONS AND FIELDS OF EMPLOYMENT**

ETRUSCA is a slaked-lime-based mineral paint characterized by a non-filming appearance and a high perspiration degree which allows to obtain a special old-like effect. It is suitable for both indoor and outdoor environments and is specifically employed for the protection and decoration of particularly important buildings under the historical and architectural point of view. Thanks to slaked lime features (long drying), ETRUSCA produces some special chromatic effects, typical of the “old paints”. It is also endowed with an excellent permeability to water vapour and a natural anti-mould power thanks to its high acidity levels.

**COMPOSITION**

Long-seasoning slaked lime, micronized calcareous charges, pigments resistant to UV rays, additives.

**METHODS OF APPLICATION**

Fine mortar slaked-lime-based supports (free of cement) are suitable for this product. They must be absolutely natural and perfectly dry and cohesive.

Wet the support about 30 minutes before the application, dilute the product with about 40-50% of water and apply the first coat with a paintbrush. Apply the second coat after minimum 2 maximum 12 hours after the first one. If a light-and-shade effect is required, apply a third coat of product using a sponge with the shading technique.

Do not apply on supports that clearly present infiltrating or rising damp.

**TECHNICAL DATA**

SPECIFIC WEIGHT:	1,660 Kg./lt. +/- 0,5%
VISCOSITY:	thixotropic paste
DRYING:	about 2 hours at 20°C to the touch – completely dry in 24 hours at 20°C
TEMPERATURE OF APPLICATION:	between 5°C and 30°C
YIELD:	0,300 – 0,400 lt./ m <sup>2</sup> (for two coats)
COLOURS:	to be chosen in the catalogue
PACKAGE:	14lt.-polyethylene cases available
PRESERVATION:	24 months in the intact packages away from temperature changes

**ITEM OF SPECIFICATIONS**

Decoration and protection of indoor and outdoor surfaces with a slaked-lime-based paint, like ETRUSCA produced by Spiver Ltd., containing long-seasoning slaked lime, micronized calcareous charges, pigments resistant to UV rays and additives; the product yield is 0,400 lt./ m<sup>2</sup> (for two coats) with a paintbrush application according to the desired effect and the required colour.

Price inclusive of the material and implementation, except the scaffoldings per square metre: €.....

N.B. The above-mentioned data are susceptible of variations. Spiver Ltd. is not responsible for any negative result depending on the application of the product out of the Company’s control and on the agents unrelated to the product quality.