



ARTHE CERA TOP

SCHEDA
TECNICA

Rev. 0 – Ed. 1

SPECIFICATIONS AND FIELDS OF EMPLOYMENT

Transparent water paste wax, for the protection of specific synthetic and Venetian plaster with lime. Produces a higher gloss polished stucco which proves the wash ability and water resistance gives a greater uniformity of final color. ARTHE WAX TOP is colored with dyes ARTHE CONCENTRATE and / or coloring of our GLOBAL SYSTEM SYSTEM

COMPOSITION

Special emulsion water based wax, non-toxic additives

METHOD OF APPLICATION.

- apply directly on the stucco finish with and polished with a stainless steel spatula, with a very low thickness
- leave to absorb and dry at least 2 hours
- proceed to final leveling always with a stainless steel spatula

TECHNICAL DATA

SPECIFIC WEIGHT: 0,962 Kg./Lt. +/- 1%
VISCOSITY: Thixotropic paste
DRYING: dry to the touch: 2 hours at 20°, completely dry 24 hours at 20°,
APPLICATION TEMPERATURE: between 5°C and 30°C
YIELD: 20 – 25 mq./Lt
COLOURS: transparent
PACKAGE: ml 750, Lt. 4 polyethylene containers
PRESERVATION 24 months in the intact packages, away from temperature changes

ITEM OF SPECIFICATIONS

Protection of wall surfaces in Venetian stucco with paste water based wax of the type ARTHE WAX TOP of SPIVER Ltd.
A special waxes in aqueous emulsion, non-toxic additives.
Price includes materials and installation, excluding scaffolding sqm. €

NB The above-mentioned data are susceptible of variations. Spiver Ltd. is not responsible for any negative result depending on the application of the product out of the Company's control and on the agents unrelated to the product quality.